



Raptor+

GLUNZ & JENSEN 



work positive

COMPACT. RELIABLE. EASY TO USE.

The Raptor+ processor is the ideal processing solution for any medium segment printers.

The Raptor+ processor offers many of the same features and benefits as the InterPlater HDX in a smaller footprint, targeting customers in the medium segment. This means that Raptor+ offers a high level of configuration flexibility and can be adapted to a wide range of applications, to better match the individual needs of the printer.

It is prepared for full unattended operation and can be used in an automated prepress line, fully integrated with both CtP and post processor plate automation. Raptor+ combines reliability, flexibility and automation to meet the needs of any customer in the medium segment.

Customers looking for high productivity or high production volume, should consider the InterPlater HDX.



Raptor+ Thermal

For traditional thermal plates with developer, wash, gum and dryer steps. Available in two widths, 68 and 85 cm.



Raptor+ Polymer

For violet photopolymer plates with pre-heat, pre-wash, developer, wash, gum and dryer steps. Very accurate hot-air preheat concept. Easily converted for violet chemfree technology.



Raptor+ Chemfree

For violet chemfree applications. Dedicated models for Fuji Pro-V and Agfa N92-VCF applications. Alternatively, use the traditional photopolymer processor with appropriate modification kit.






Easy to operate graphic touch screen with logical menu. Optional native language plug-in and built-in remote support and diagnostics.



Replenishment is precisely calculated based on processed square meters and time, maintaining stable, waste-free processing.



All electrical and mechanical components are located on the sides of the processor, for easy and convenient access during maintenance.



Rollers and brushes are mounted with snap lock bearings, so they can be instantly replaced without tools or the need to re-calibrate pressure.



Maintenance-free worm gears drive the rollers and provide smooth and trouble free plate transport inside the processor.



Easy-lift top covers provide good access to the inside of the processor. The electronics are conveniently located on the side of the processor.

The filter house is conveniently mounted under the frame, giving easy access to the cooling unit and extra storage space for containers.



	Raptor+ T		Raptor+ P		Raptor+ Chemfree
MODEL	68	85	68	85	85
PERFORMANCE					
Market position	Medium capacity		Medium capacity		Medium capacity
Plate types	Thermal plates		Violet photopolymer plates or Violet chemfree plates with Chemfree Conversion kit		Violet chemfree plates
Plate width (max)	680 mm (26.8")	850 mm (33.5")	680 mm (26.8")	850 mm (33.5")	850 mm (33.5")
Plate length (min)	274 mm (10.8")		274 mm (10.8")		274 mm (10.8")
Plate thickness	0.15-0.3 mm (0.006-0.012")		0.15-0.3 mm (0.006-0.012")		0.15-0.3 mm (0.006-0.012")
Processing speed	40-140 cm/min (15.7-55.1"/min)		40-140 cm/min (15.7-55.1"/min)		100 cm/min (39.4"/min)
CONSUMPTION					
Tank capacity (developer)	17 l (4.5 US gal)	22 l (5.8 US gal)	17 l (4.5 US gal)	22 l (5.8 US gal)	22 l (5.8 US gal)
Temperature range (pre-heat)	N/A		70-140 °C (158-284 °F)		70-140 °C (158-284 °F)
Temperature range (developer)	20-40 °C (68-104 °F)		20-40 °C (68-104 °F)		20-34 °C (68-93 °F)
Water (draining)	14 l/min (3.7 US gal/min)	16 l/min (4.2 US gal/min)	28 l/min (7.4 US gal/min)	32 l/min (8.4 US gal/min)	N/A
Water (recirculating)	0.2 l/min (0.8 US gal/min)	0.2 l/min (0.8 US gal/min)	0.7 l/min (2.7 US gal/min)	0.7 l/min (2.7 US gal/min)	N/A
Power (stand-by)	0.06 kW (200 BTU/hour)		1.2 kW (4,000 BTU/hour)		1.1 kW (3,600 BTU/hour)
Power (operate)	1.8 kW (6,000 BTU/hour)		3.6 kW (12,000 BTU/hour)		2.6 kW (8,870 BTU/hour)
GENERAL					
Dimensions (LxWxH)	115 x 108 x 101-110 cm (45.3 x 42.5 x 39.8-43.3")	115 x 126 x 101-110 cm (45.3 x 49.4 x 39.8-43.3")	195 x 108 x 101-110 cm (76.8 x 42.5 x 39.8-43.3")	195 x 126 x 101-110 cm (76.8 x 49.4 x 39.8-43.3")	134 x 126 x 101-110 cm (52.8 x 49.4 x 39.8-43.3")
Weight	190 kg (419 lbs)	235 kg (518 lbs)	265 kg (584 lbs)	307 kg (677 lbs)	234 kg (514 lbs)
Approvals	UL, c-UL certified. Complies with CE standards and RoHs directive.				
Standard	Configured for typical applications in developer, Automatic container level alarm, Universal front panel, World-wide electrical configurable, Graphical finger touch control panel, Cooling unit, standard capacity 50/60 Hz, Hand shower for easy cleaning				
Accessories	Closed stand, Drip tray, Delivery table (L = 710 mm), Feed table (L=400 mm), Dedicated application configuration kits, Online interfaces for CtP, Remote Enabling System, Water saving, USB Memory stick, Stackers				



Preventive Maintenance Kits are available for this product to maximize production uptime.

GLUNZ & JENSEN

Glunz & Jensen A/S
 Haslevvej 13
 DK-4100 Ringsted, Denmark
 +45 5768 8181
 gj@glunz-jensen.com

Glunz & Jensen, Inc.
 12633 Industrial Drive
 Granger, IN 46530, USA
 +1 574 272 9950
 gj-americas@glunz-jensen.com

Glunz & Jensen Rep. Office
 Shenzhen 518111, P.R. China
 +852 9230 2919 (HK)
 +86 186 1199 2587 (CH)
 gj-china@glunz-jensen.com

www.glunz-jensen.com